



Republic of the Philippines
BANGSAMORO AUTONOMOUS REGION IN MUSLIM MINDANAO
OFFICE OF THE CHIEF MINISTER
SPECIAL BIDS AND AWARDS COMMITTEE
MARAWI REHABILITATION PROGRAM
Bangsamoro Government Center, Governor Gutierrez Avenue, Rosary Heights VII, Cotabato City 9600

**IN RE: SUPPLY AND DELIVERY OF WATER TRUCK
FOR THE MARAWI REHABILITATION PROGRAM -
PROGRAM MANAGEMENT OFFICE (MRP-PMO)**

ABC: PHP 5,500,000.00

IB NO.: MRP-052023-07

X-----X

SUPPLEMENTAL BID BULLETIN NO. 2023-05-011
May 26, 2023/Dhu'l-Qidah 6, 1444 AH

Pursuant to the Revised Implementing Rules and Regulations of Republic Act No. 9184 otherwise known as the Government Procurement Reform Act, please be advised of the following clarifications and Modifications on the Bidding Documents with respect to the subject procurement.

SUBJECT	ORIGINAL	AMENDED
1. Technical Specifications	(KINDLY REFER TO ANNEX "A")	(KINDLY REFER TO ANNEX "B")

This Supplemental/Bid Bulletin is issued to modify or amend the corresponding items in the Bidding Documents.

For guidance and information of all concerned.


NARCISA D. MACOG
Chairperson, Special Bids and Awards Committee

Technical Specifications

SUPPLY AND DELIVERY OF WATER TRUCK FOR THE MRP-PMO

NAME OF BIDDER: _____

Item No.	Description	Quantity	Unit	Statement of Compliance
1	<p>Water Truck</p> <p>Specifications:</p> <ul style="list-style-type: none">• Chassis Parameters• Overall Dimension (mm) : 7800*2200*2450• Minimum Gross weight (without load) (kg) : 7,300• Minimum Kerb weight (kg) – without load : 3,760• Wheelbase (mm) : 3,360• Driving Type : 4*2• Steering : Mechanical circular ball• Tires Size : 8.25 - 16PR• Number of Tires : 6+1• Passengers in cab : 3 • Engine• Power : 190HP• Max Speed (km/h) : 95• Emission Standard : EURO 4,5,6• Number of Cylinders : At least 4-cylinder• Displacement : 3000-4500 cc• Transmission : 6-Speed, 1 Reverse • Water Tanker Performance• Tanker body / capacity : 8,000L• Body Material : Weather Resisting Steel• Tanker shape : Ellipse as standard• Water Pump : 7.5hp - discharge• Washing Width : ≥20 M• Washing Speed : 5-20 km/h• Rear Cannon Ranger : ≥50 M• Hose : 2.5” x 50ft Double Jacket Hose with• Adjustable Nozzle• Spray Bar : Front, Side and Rear• Manhole, Access ladder, walkway and handrail: Equipped• Painting : Two Primers and 1 final paint coating• Color and Logo : According to Procuring Entity’s preference	1	Units	

	<ul style="list-style-type: none">• Control Panel : English• Brakes System• Services Brakes : Full air, dual circuits, “S” cam type,• leading and trailing shoes for front and rear• Power Steering : Required• Clutch Booster : Required• Engine Tachometer : Required• <i>Note:</i> Supplier must consider the additional load of 8000 L of Water on the maximum gross weight.			
--	---	--	--	--

I hereby certify that the statement of compliance to the foregoing technical specifications are true and correct, otherwise, if found to be false either during bid evaluation or post qualification, the same shall give rise to automatic disqualification of our bid.

Name of Company/Bidder

Signature over Printed Name
Authorized Representative

Date

Technical Specifications

SUPPLY AND DELIVERY OF WATER TRUCK FOR THE MRP-PMO

NAME OF BIDDER: _____

Item No.	Description	Quantity	Unit	Statement of Compliance
1	<p>Water Truck</p> <p>Specifications</p> <ul style="list-style-type: none">Chassis ParametersOverall Dimension (mm) : 7800*2200*2450<u>Minimum Gross weight (without load) (kg) : 7,300</u><u>Minimum Kerb weight (kg) – without load : 3,760</u>Wheelbase (mm) : 3,360Driving Type : 4*2Steering : Mechanical circular ballTires Size : 8.25 - 16PRNumber of Tires : 6+1Passengers in cab : 3 EnginePower : 190HPMax Speed (km/h) : 95Emission Standard : EURO 4,5,6Number of Cylinders : At least 4-cylinderDisplacement : 3000-4500 ccTransmission : 6-Speed, 1 Reverse Water Tanker PerformanceTanker body / capacity : 8,000LBody Material : Weather Resisting SteelTanker shape : Ellipse as standardWater Pump : 7.5hp - dischargeWashing Width : ≥20 MWashing Speed : 5-20 km/hRear Cannon Ranger : ≥50 MHose : 2.5” x 50ft Double Jacket Hose withAdjustable NozzleSpray Bar : Front, Side and RearManhole, Access ladder, walkway and handrail: EquippedPainting : Two Primers and 1 final paint coatingColor and Logo : According to Procuring Entity’s preference	1	Units	

- | | | | |
|---|--|--|--|
| <ul style="list-style-type: none">• Control Panel : English• Brakes System• Services Brakes : Full air, dual circuits, “S” cam type,• leading and trailing shoes for front and rear• Power Steering : Required• Clutch Booster : Required• Engine Tachometer : Required• <u>Note: Supplier must consider the additional load of 8000L of Water on the maximum gross weight.</u> | | | |
|---|--|--|--|

I hereby certify that the statement of compliance to the foregoing technical specifications are true and correct, otherwise, if found to be false either during bid evaluation or post qualification, the same shall give rise to automatic disqualification of our bid.

Name of Company/Bidder

Signature over Printed Name
Authorized Representative

Date